

POWERWARE 5115 RACKMOUNT UPS TECHNICAL SPECS

Powerware 5115RM				
Rating	500 VA	750 VA	1000 VA	1500 VA
Part number	103003267-6591	103003270-6591	103003273-6591	103003276-6591
Capacity (VA/watts)	500/320	750/500	1000/670	1500/1000
Dimensions WxDxH (mm)	440x580x45			
Weight (kg)	9	15	15	19
Input connection	IEC320/10A			
Output connection	4xIEC320/10A			
Typical runtime (full load)	5 min	6 min	5 min	5 min
Typical runtime (Half load)	15 min	17 min	15 min	15 min

Operational

Nominal input voltage (Vac)	220/230/240 Vac
Input voltage range	(+/-20% of nominal)
Operating frequency	50/60 Hz auto sensing
Nominal output voltage	220/230/240 Vac
Output voltage regulation	-10%/+6% of selected nominal Voltage
Overload capacity	110% 3 min; 150% 10 cycles
Efficiency	95%

User interface

LED	Four LEDs; UPS on, UPS on battery, overload, alarm
Standard communication ports	RS232/USB and X-slot
Optional	Internal SNMP adapter

Environmental

Operating Temperature	0°C to +40°C
Storage Temp	-15°C to 55°C
Altitude	< 3000 M
Audible Noise	< 40 dB

Certification

Markings	CE
Safety	EN 50091-1-1 & UL 1778
EMC	EN 50091-2, EN6100-3-2

BATTERY RUNTIMES

Load (VA/Watts)	PW5115 RM 500(i)	PW5115 RM 750(i)	PW5115 RM 1000(i)	PW5115 RM 1500(i)
200 / 130	17	38	41	76
300 / 190	11	27	28	58
500 / 320	5	14	15	28
600 / 400		9	10	19
750 / 520		6	8	14
900 / 600			6	10
1000 / 670			5	8
1200 / 800				6
1440 / 1000				5

Note: Battery run times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

AVAILABLE OPTIONS

Part Number	Description
05146447-5502	X-slot Multi-Server Card
1018460	X-slot AS400/Relay Card
116750221-001	X-slot Web/SNMP Card
103002510-5501	X-slot Modbus Card